
POTENTIOMETRIC SURFACE MAP OF THE BEDROCK AQUIFERS OF MARTIN COUNTY, INDIANA



Martin County is located in southwestern Indiana, and is bounded by the counties of Greene, Lawrence, Orange, Dubois, and Daviess to the north, northeast, east, south and west, respectively. The majority of the county lies within the East Fork White River Basin with a portion in the northwest situated in the White and West Fork White River Basin. Additionally, a relatively small area in the southeast corner of the county is located in the Patoka River Basin.

The potentiometric surface is a measure of the pressure on groundwater in a water bearing formation. Wells are completed in aquifers at various depths, and typically, under confined conditions (bounded by impermeable layers above and below the water bearing formation). However, some wells are completed under unconfined (not bounded by impermeable layers) settings. Water in a confined aquifer, which is under hydrostatic pressure, will rise in a well above the top of the water bearing formation. In contrast, groundwater in an unconfined aquifer, which is at atmospheric pressure, will not rise in a well above the top of the water bearing formation.

Static water-level measurements obtained from individual wells used to construct county potentiometric surface maps are indicative of the water-level at the time of well completion. The groundwater level within an aquifer constantly fluctuates in response to rainfall, evapotranspiration, groundwater movement and pumpage. Therefore, measured static water-levels in an area may differ due to local or seasonal variations. Because fluctuations in groundwater are typically small, static water-levels can be used to construct a generalized potentiometric surface map. As a general rule, but certainly not always, groundwater flow approximates the overlying topography and intersects the land surface at major streams.


The potentiometric surface map of the bedrock aquifers was mapped by contouring the elevations of 232 static water-levels reported on well records received primarily over a 50 year period. Universal Transverse Mercator (UTM) coordinates, used in locating the water wells, were either physically obtained in the field, determined through address geocoding, or reported on water well records. The location of the majority of the water well records used to make the potentiometric surface map were field verified. Elevation data were obtained from a digital elevation model. Quality control/quality assurance procedures were utilized to refine or remove data where errors were readily apparent.


Potentiometric surface elevations range from a high of 520 feet mean sea level (msl) northeast of West Boggs Lake in the west-central portion of the county, to a low of 420 feet msl in the southwest portion of the county along the East Fork White River. Regional groundwater flow is generally to the south towards the East Fork White River and tributaries.

Potentiometric contours have not been extended through portions of the county that are lacking in data and/or covered by more prolific unconsolidated deposits which limits the necessity to complete wells in the

The county potentiometric surface map can be used to define the regional groundwater flow path and to identify significant areas of groundwater recharge and discharge. These maps represent overall regional characteristics and are not intended to be a substitute for site-specific studies.


EXPLANATION Line of equal elevation, in feet above mean sea level Potentiometric Contour interval 10 feet Basin Boundary **US Highway** Municipal Boundary State Managed Property US Federal Managed Property Lake & River No Aquifer Material or Limited Data











Map Use and Disclaimer Statement

We request that the following agency be acknowledged in products derived from this map: Indiana Department of Natural Resources, Division of Water.

This map was compiled by staff of the Indiana Department of Natural Resources, Division of Water using data believed to be reasonably accurate. However, a degree of error is inherent in all maps. This product is distributed "as is" without warranties of any kind, either expressed or implied. This map is intended for use only at the published scale.

This map has been created from several existing shapefiles. Township and Range Lines of Indiana (line shapefile, 20020621), Land Survey Lines of Indiana (polygon shapefile, 20020621), and County Boundaries of Indiana (polygon shapefile, 20020621) are from the Indiana Geological Survey and based on a 1:24,000 scale. Roads (TIGER and INDOT) (line shapefile, 2005) is from the Indiana Department of Transportation and based on a 1:24,000 scale. System1 (line shapefile, 2003) is from the Indiana Department of Transportation and based on a 1:24,000 scale. Incorporated Boundaries in Indiana (polygon shapefile, 20060501) is from the Graphics and Engineering Section Indiana Department of Transportation. Hydrography, Streams (NHD) (line shapefile, 20081218), Rivers (NHD) (polygon shapefile, 20081218), and Lakes (NHD) (polygon shapefile, 20081218) are from the U.S. Geological Survey and based on a 1:24,000 scale. Basin boundaries are modified from the Watershed Boundary Dataset (polygon shapefile, 2008) developed by the Natural Conservation Service and based on a 1:24,000 scale. Managed Lands IDNR IN (polygon shapefile, 20100920) is from the Indiana Department of Natural Resources and based on a 1:24,000 scale. Digital Elevation Model image is derived from the Indiana Ortho/LiDAR Statewide Collection Program (2013). Martin County Bedrock No Aquifer Material or Limited Data (polygon shapefile, Grove, 2019), and Potentiometric Surface Map of the Bedrock Aquifers of

Martin County, Indiana (line shapefile, Grove, 2019) are based on a 1:24,000 scale.

Potentiometric Surface Map of the **Bedrock Aquifers of Martin County, Indiana**

Glenn E. Grove Division of Water, Resource Assessment Section February 2019

Division of Water