


GENERAL NOTES

1. Unless otherwise specified, channelizing devices shall be spaced as shown on Standard Drawing E 801-TCLG-01.
- ② Reflectorized bands may be omitted from cones for lane closures during daylight hours.
- ③ For vertical panels greater than 3 ft in height, the width of the stripes shall be 6 in.
- ④ Vertical panels used on an expressway or a freeway shall have a minimum reflective panel area of 270 sq. in. Other roadways with a posted speed limit of 50 mph or greater shall have a minimum reflective panel area of 270 sq. in., also.
- ⑤ Cones shall have a minimum height of 2'-4" when used at night.
- ⑥ The maximum distance between the edges of adjacent reflective sheeting strips shall be 2 in.
7. Panel and direction indicator barricades and supports shall meet NCHRP 350 crash evaluation criteria.
- ⑧ Minimum flexible tubular marker base area shall be 0.3 sq. ft.
- ⑨ It is not necessary to delineate a drop-off of 3 in. or less adjacent to active travel lanes. Where channellizing devices are used to delineate drop-offs of 3 in. or less adjacent to active travel lanes, at least 33 in. of the device shall be above the adjoining pavement surface. Where channelizing devices are used to delineate a drop-off greater than 3 in. adjacent to active travel lanes, at least 27 in. of the device shall be above the adjoining pavement surface and a Type C warning light shall be attached to the top of the device (on the pavement side). In no case shall more than 9 in. of the device be below the adjoining pavement surface.
10. The proper orientation in respect to approaching vehicular traffic shall be maintained on vertical panels. Drums are the preferred channelizing device in a tight radius curve.

LEGEND

- - Device may be used in tangent set-ups.
- X - Device may be used in taper or transition set-ups.
- ⊗ - Devices may be used in two-way traffic set-ups to divide opposing lanes of traffic.
- - Device may be used to divide two or more lanes of traffic in the same direction.
- ⊙ - Device may be used to replace barricades and drums where space is limited.
- ◻ - Device may be used to delineate edge of pavement drop-off where space is limited.

INDIANA DEPARTMENT OF TRANSPORTATION	
CHANNELIZING DEVICES	
SEPTEMBER 2005	
STANDARD DRAWING NO. E 801-TCDV-02	
 REGISTERED No. 9750 STATE OF INDIANA PROFESSIONAL ENGINEER	/s/ Richard L. VanCleave 9-01-05 DESIGN STANDARDS ENGINEER DATE
	/s/ Richard K. Smutzer 9-01-05 CHIEF HIGHWAY ENGINEER DATE
DESIGN STANDARDS ENGINEER	