



**TYPICAL PARTIAL CONCRETE BRIDGE RAILING
TYPE TF-2 ELEVATION VIEW**

(WITHOUT INLET PLACEMENT SHOWN;
WITH INLET PLACEMENT SIMILAR)

NOTES

1. SPACING OF JOINTS IN TUBE STEEL
MAXIMUM: 40 FT MINIMUM: 20 FT
2. POST SPACING MAXIMUM: 7'-6"
MINIMUM: 4'-0"
3. DISTANCE FROM CENTERLINE OF SPLICING
TO CENTERLINE OF RAILING POST: MAXIMUM: 30"
MINIMUM: 18"
4. RAILING POST TO EDGE OF OPEN JOINT IN RAILING.
5. Pay limits for concrete bridge railing Type TF-2 to end of railing.

INDIANA DEPARTMENT OF TRANSPORTATION											
CONCRETE BRIDGE RAILING TYPE TF-2											
SEPTEMBER 2005											
STANDARD DRAWING NO. E 706-BRTF-07											
	<table style="width: 100%; border: none;"> <tr> <td style="border: none;">/s/ Richard L. VanCleave</td> <td style="border: none; text-align: right;">9-01-05</td> </tr> <tr> <td style="border: none;">DESIGN STANDARDS ENGINEER</td> <td style="border: none; text-align: right;">DATE</td> </tr> <tr> <td colspan="2" style="border: none;"> </td> </tr> <tr> <td style="border: none;">/s/ Richard K. Smutzer</td> <td style="border: none; text-align: right;">9-01-05</td> </tr> <tr> <td style="border: none;">CHIEF HIGHWAY ENGINEER</td> <td style="border: none; text-align: right;">DATE</td> </tr> </table>	/s/ Richard L. VanCleave	9-01-05	DESIGN STANDARDS ENGINEER	DATE			/s/ Richard K. Smutzer	9-01-05	CHIEF HIGHWAY ENGINEER	DATE
/s/ Richard L. VanCleave	9-01-05										
DESIGN STANDARDS ENGINEER	DATE										
/s/ Richard K. Smutzer	9-01-05										
CHIEF HIGHWAY ENGINEER	DATE										
DESIGN STANDARDS ENGINEER											