Material	Pipe Type				
	1	2	3	4	5
Non-Reinforced Concrete Pipe, Class 3 (S)	X	х	х		
Non-Reinforced Concrete Pipe				х	
Reinforced Concrete Pipe (S)	х	X	х		
Reinforced Concrete Horizontal Elliptical Pipe (S)	X	X	х		
Corrugated Steel Pipe (C)	Х		х		Х
Polymer Precoated Galvanized Corrugated Steel Pipe (C)	х		х		Х
Polymer Precoated Galvanized Corrugated Steel Pipe Type IA (S)	Х	х	х		Х
Fully Bituminous Coated and Lined Corrugated Steel Pipe (S)		х			х
Corrugated Steel Pipe-Arch (C)	Х		х		Х
Polymer Precoated Galvanized Corr. Steel Pipe Arch Type IIA (S)	x	х	x		х
Fully Bituminous Coated and Lined Corrugated Steel Pipe-Arch (S)		х			х
Polymer Precoated Galvanized Corrugated Steel Pipe-Arch (C)	X		х		Х
Corrugated Aluminum Alloy Pipe (C)	X		х		Х
Corrugated Aluminum Alloy Pipe-Arch (C)	х		х		х
Structural Plate Steel Pipe (C)	х		х		
Structural Plate Steel Pipe-Arch (C)	Х		х		
Structural Plate Aluminum Alloy Pipe (C)	х		х		
Structural Plate Aluminum Alloy Pipe-Arch (C)	х		х		
Spiral Rib Steel Pipe (SS)	Х		х		Х
Clay Pipe, Extra Strength (S)	Х	х	х		
Clay Pipe				х	
Perforated Clay Pipe				х	
Concrete Drain Tile				х	
Clay Drain Tile				х	
Corrugated Polyethylene Pipe, Type SP				х	
Corrugated Polyethylene Pipe, Type (S)	х	х	х	х	х
Profile Wall (Ribbed) Polyethylene Pipe (S)	х	х	х		х
Profile Wall (Closed) Polyethylene Pipe (S)	х	х	х		х
Smooth Wall Polyethylene Pipe (S)	х	х	х		х
Corrugated Polyethylene Drainage Tubing				х	
Corrugated Polypropylene Pipe (S)	x	х	х		х
Perforated PVC Semicircular Pipe				х	
Profile Wall PVC Pipe (S)	х	х	х	х	х
Smooth Wall PVC Pipe (S)	х	х	х		х

NOTES:

- 1. The prescribed uses for the pipe types are as follows.
 - Type 1 Pipe Culverts under mainline pavement and public road approaches.
- b. Type 2 Pipe Storm sewer pipe.
- c. Type 3 Pipe Culverts under driveways and field entrances.
- d. Type 4 Pipe Drain tile and longitudinal underdrains.
- e. Type 5 Pipe Broken back and other installations requiring coupled pipe.
- See to Standard Drawlngs E 715-PHCL-01 through E 715-PHCL-25 and E 717-PHCL-01 through E 717-PHCL-10 for allowable heights of cover for various pipe materials except Type 4 pipes.
- See to Standard Drawings E 715-PSLC-01 through E 715-PSLC-03 for required pipe service life criteria.
- 4. Any pipe material which is in accordance with the designated pipe type, acceptable for height of cover conditions, and conforms to service life criteria may be installed.

LEGEND:

- (C)- Corrugated Interior Culvert Pipe
- (S)- Smooth Interior Culvert or Storm Sewer Pipe
- (SS)- Seml-Smooth Interior Culvert Pipe

INDIANA DEPARTMENT OF TRANSPORTATION

PIPE CLASSIFICATION TABLES

SEPTEMBER 2017


STANDARD DRAWING NO. E 715-PIPE-01



/s/ Elizabeth W. Phillips 03/22/17
DESIGN STANDARDS ENGINEER DATE

 /s/ John Leckie
 04/10/17


 CHIEF ENGINEER
 DATE



MULTIPLE INSTALLATION

NOTES:

- (1) In order to maintain their manufactured shape, all 3" x 1" corrugated steel pipe-arch sections shall have wire ties attached at each end as shown in the detail. The wire ties shall be attached across the largest vertical and horizontal dimension of the pipe-arch. the wire ties shall be installed by the manufacturer and shall remain in place until the onsite installation is complete.
- (2) WWR shall be wired to every second circumferential bolt and every twelfth longitudinal bolt.




STRUCTURAL PLATE PIPE-ARCH CULVERT ELEVATION

STEEL PIPE-ARCH SECTIONS

END STABILIZATION OF 3" x 1" CORRUGATED (1)

STRUCTURAL PLATE PIPE CULVERT



TYPICAL LONGITUDINAL SECTION

CONCRETE FIELD PAVED INVERT DETAILS

INDIANA DEPARTMENT OF TRANSPORTATION

MISCELLANEOUS PIPE DETAILS

SEPTEMBER 2017

STANDARD DRAWING NO. E 715-PIPE-02



/s/ Elizabeth W. Phillips 03/22/17
DESIGN STANDARDS ENGINEER DATE